


MONUMENT RECORD  
Corner ID: InCr\_K11  
Section Corner  
Section 16- T07N-R02W, 2nd P.M.  
Indian Creek Township, Monroe County, Indiana



EXISTING SURVEY HISTORY

Include as much detail and history of the corner as known at the time of perpetuation.

SUBSEQUENT CORNER RESTORATION:

Date Surveyed: 01/10/2012 By: Kevin P. Enright  
Where filed or recorded: M.C.S.O. Records  
Original monument: 5/8” Dia Rebar with “Deckard” Cap  
Bearing Trees or Reference Monuments:

Species	Bearing	Distance
4x4” Post	S 03° E	3.26’
Mag in 6x6” Post	S 84° W	16.29’
Sandstone	N 26° E	96.0’

Notes:

**SURVEY EVIDENCE FOUND:** Include evidence found and weighed, search area or areas, search procedure, etc.  
Date of Search: 02/25/22 By: Z.W. & K.H. Monument Found: 5/8 inch diameter rebar stamped “Deckard” BTs or Reference Objects Found: 4x4” Wood Post and Mag nail in 6x6” Wood Post.

**OTHER SURVEY HISTORY:** Include details such as surveyor name, date, recording info, monument description, etc.

- Eric L. Deckard set a rebar in a Type “E” Administrative Subdivision for Hollingsworth dated March 19<sup>th</sup>, 2008 (Job Number 08-09)
- Eric L. Deckard referenced a “Deckard” rebar in a survey for McConnell dated January 12<sup>th</sup>, 2017. (Job Number 16-140)
- Raymond Graham referenced the NE corner of the NE quarter of the SW quarter of Section 16, Township 7 North, Range 2 West in a survey for a 5.00 acre tract dated September 27<sup>th</sup>, 1991.

PERPETUATION RECORD

**MONUMENT:** Describe monument set or found (Include material type, scribing, distance above/below grade, dimensions.)  
5/8 inch diameter rebar with cap stamped “Deckard” found 1 inch above grade.

**OTHER EVIDENCE:** Describe corner location relative to nearby features and how to reach the corner location – note fences, roads, timber cutting lines, mow lines, clearings, plantings, streams, topo changes, etc.  
East-West running wire fence was found to the South of the rebar and North-South running wire fence was found to the West of the rebar.

**THEORY OF LOCATION:** Describe the theory of location for acceptance of this monument with reference to the recording information for the survey upon which this record is derived. Said recorded survey shall be certified by the same professional surveyor who certifies this document, shall identify and accept this monument, and shall have been recorded within (3) years of Form submittal.  
This rebar was set by Eric L. Deckard for Hollingsworth dated March 19<sup>th</sup>, 2008 and found in Deckard Land Surveying Job Number (08-09). This rebar was found to be commonly accepted by surveys in the area and was accepted and held as said corner as shown on Keith & Trudy McConnell - Boundary Survey on file at the Monroe County Recorder's Office as Instrument Number 2022003967.

**MONUMENT PRESERVATION:** Describe work done to preserve existing monument. Stone mounds should be placed around monuments when stones are readily available. Paint corner stones but not the scribing. A Monroe County “PROTECT NEARBY SURVEY MARKER” sign shall be attached to a steel post when practicable. Note location and relation of corner to sign.  
Monroe County “PROTECT NEARBY SURVEY MARKER” sign was attached to 4x4 inch diameter wood post South 10 degrees East 3.11 feet from the rebar.

**GEODETIC COORDINATES:** Northing: 1382480.9, Easting: 3079260.3

**BASIS OF GEODETIC COORDINATES:** Describe equipment, date, and personnel used to collect coordinates, datum, epoch, geoid and zone.  
Coordinates shown hereon were obtained from GPS observations utilizing the Indiana Real-Time Network (INCORS). Indiana West Zone, NAD83(2011) Epoch 2010.0000, State Plane Grid Coordinates, US Survey Feet. Geoid model G2012BU7. Datum NAD83\_NO\_TRANS and the use of a Topcon GT Robotic Total Station by Zachary Waggoner and Kyle Hazelman on February 25<sup>th</sup>, 2022.




MONUMENT RECORD

Corner ID: InCr\_K11

Section Corner

Section 16- T07N-R02W, 2nd P.M.

Indian Creek Township, Monroe County, Indiana



**WITNESS MONUMENT TIES:** Describe at least three new BT's and/or witness objects established or work done to preserve existing evidence. The following procedures are provided for guidance. Please utilize professional judgment when choosing witness ties. All ties to BT's should be a magnetic nail and washer (state what kind) set in a hack mark at root crown (less than 12" above ground) perpendicular to center of tree unless otherwise noted. All monuments should be tied to at least three accessories with a minimum of 60° of separation. BTs should be healthy with a minimum DBH of 4". BT description should include tree species, diameter at 4.5' above ground, distance of nail above ground, and description of nail location (e.g.. SE side of root). Note bearing from monument to the center of the BT, distance to the nail. Other survey monuments that were located in the vicinity and their relation to the monument may also be included.

ID	Bearing	Distance	Description
B	S 10° E	3.11'	4x4" Dia. Wood Post with sign on N side
C	S 82° W	16.4'	Mag w/ washer found 5" A.G. in N side of 6x6" Dia. Wood Post
D	N 20° W	38.45'	Mag w/ washer set 7" A.G. in E side of 4x4" Dia. Wood Post

**MONUMENT LOCATION SKETCH:** Optional: Attach a sketch or aerial image. Monument sketch is not required for reimbursement.



**PHOTO IDENTIFIED:** Photograph close up photo of monument and a vicinity photo of the monument that includes the Monroe County “PROTECT NEARBY SURVEY MARKER” sign. Provide photo orientation and date. Additional photos may be included by clicking the “+” button at the end of the horizontal line.

Photo Date: **FEBRUARY 2022**




Photo Orientation & Description: **Looking South at K-11**



Photo Orientation & Description: **Looking East at K-11**



MONUMENT RECORD  
Corner ID: InCr\_K11  
Section Corner  
Section 16- T07N-R02W, 2nd P.M.  
Indian Creek Township, Monroe County, Indiana



FIELD PERSONNEL:

Field Date: 02/25/22 By: Z.W.. & K.H. Project #: 21-157 Field Book: , page: Notes:

CERTIFICATION:

Professional Surveyor Name: Eric L. Deckard  
Indiana Professional Surveyor No.: 29900012  
Firm Name: Deckard Land Surveying  
Date: 03/07/22

Signature:

Date:

Signature:



Seal:

OFFICE USE ONLY

NOTICE TO PROCEED AND MONUMENT RECORD FORM ISSUED TO:			
Offeror Name: Eric Deckard		Firm Name: Deckard Land Surveying, LLC	
Phone: 812-961-0235		Email: Ericdeckard1@msn.com	
Corner Classification: 1/4 Corner		Corner Coordinate Status: Perpetuated	
Issue Date: 03/02/2022	Form Due Date: 03/02/2022	Form Receipt Date: 03/02/2022	

COUNTY SURVEYOR APPROVAL:		
<input checked="" type="checkbox"/> Yes, Signature:	Date: 10/25/2022	
<input type="checkbox"/> No, reasons for denial		Seal:

SURVEYOR REVIEW BOARD APPROVAL:		
<input checked="" type="checkbox"/> Yes, Signature:	Date: 10/25/2022	
<input type="checkbox"/> No, reasons for denial		Seal: